

HYDROL ZZ RANGE

Product description

Indy Hydrol ZZ is a range of high-performance zinc-free (ashless) hydraulic oils formulated to provide outstanding protection even under severe operating conditions. Indy Hydrol ZZ is formulated to give maximum performance in the most severe vane pump applications.

Application

- Ideal hydraulic fluid for piston pumps and other hydraulic applications sensitive to thermal deposit formation.
- Suitable for use in most industrial and manufacturing operations.

Features & benefits

- **Refined Additive Package**
  Unique additive technology provides excellent resistance to breakdown under thermal and mechanical stresses, resulting in reduced deposit formation and extended equipment maintenance levels.

Suitable for use for the following specifications:

- ✓ Danieli 0.000.001 Type 21
- ✓ DIN 51524 Part 1 & 2
- ✓ ISO 11158 HL & HM
- ✓ Morgan No-Twist Rod Mill
- ✓ Schuler Pressen (ex Müller Weingarten) DT 55055 01.2013

Physical Characteristics:

Properties		32	46	68
Density @20°C	$kg.m^{-3}$	880	870	870
Viscosity @40°C	(cSt)	32	46	68
Viscosity @100°C	(cSt)	5.4	6.54	8.52

Available Product Pack Sizes:

Part no.			Pack Size
32	46	68	
OIL-01115	OIL-01125	OIL-01135	1000L
OIL-01116	OIL-01126	OIL-01136	210L
OIL-01117	OIL-01127	OIL-01137	20L

G.U.D. Holdings Durban
Tel: +27 (0)31 910 3111

03 The Avenue East,Prospecton, 4133,
KwaZulu Natal, South Africa

G.U.D. Holdings Pietermaritzburg
Tel: +27 (0)33 392 9300
Tel: +27 (0)33 390 1844

info@indy.co.za
www.indyoil.co.za

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation.