

TOOLUBE 150 & 220

Product description

Indy Toolubes are premium quality pneumatic machinery lubricant that is blended from highly refined paraffinic base oils and incorporate special additives to enhance its properties.

Application

- Can be used in air driven rock drills and other pneumatic machinery.
- Specifically designed to have good demulsifying characteristics so that adequate lubrication is still provided even in the presence of wet air.

Features & benefits

- **Advanced Additive Technology**
  Provides excellent lubrication and anti-wear performance as well as high levels of corrosion protection.
  Its low pour point ensure that tools remain free from oil deposits in areas cooled by rapid air expansion.

Physical Characteristics:

Properties		150	220
Density @20°C	$kg.m^{-3}$	900	900
Viscosity @40°C	(cSt)	150	220
Viscosity @100 °C	(cSt)	14.9	23
Viscosity Index		99	129
Pour point	°C	-9	-9
Flash point	°C	240	240

Available Product Pack Sizes:

Part No.		Pack Size
220	150	
OIL-00890	OIL-00881	210L
OIL-00891	OIL-00882	20L

G.U.D. Holdings Durban
Tel: +27 (0)31 910 3111

03 The Avenue East,Prospecton, 4133,
KwaZulu Natal, South Africa

G.U.D. Holdings Pietermaritzburg
Tel: +27 (0)33 392 9300
Tel: +27 (0)33 390 1844

info@indy.co.za
www.indyoil.co.za

When used as intended, this product is not expected to pose a health risk.
Used oil may be hazardous to health and the environment—always dispose of it responsibly and in accordance with applicable legislation.